



INSTALLATION INSTRUCTIONS

RM Deluxe Cove Light

Voltage/ Power Supply:

LED

• 12v DC

- Powered by Magnetic Low Voltage Drivers
- Polarity sensitive
(red or black is positive, white or blue is negative)
 - If lights don't illuminate, try reversing leads.
 - Restore electricity & check operation of fixture.

INCANDESCENT

• 12v AC

- Both Standard (STD) & Extra Bright (EB)
- Powered by Magnetic Low Voltage Transformers

Fixtures are packed in plastic bags for protection during the shipping process. Please note tagging code if required.

! DISCONNECT THE POWER BY TURNING OFF CIRCUIT BREAKER OR REMOVING FUSE AT FUSE BOX !

! Do not plug the fixtures directly into the electrical outlet !

Installation Option 1: Mechanical Fastening

Need new copy

- Recommended clip spacing: LED: 12" intervals; Incandescent (EB and STD): 6" intervals.

Installation Option 2: Adhesive Fastening

Please ensure that the mounting area is neat, clean, dry, and free from any chemical residue. For best results, RSL recommends using a high quality construction adhesive or sealant to bond the fixture to the substrate. A continuous bead of adhesive/sealant reduces the opportunity

cont...



ROBERTS STEP-LITE SYSTEMS ■ 8100 SW 15th St. ■ Oklahoma City, OK 73128
info@robertsstemplite.com ■ www.robertsstemplite.com
405.728.4895 ■ 800.654.8268 ■ F: 405.728.4878





RM Deluxe Cove Light

continued

for the fixture to sag when fully cured. The fixture should be supported every 8-12" while the material cures- typically 24-36 hours.


Special Notes:

All electrical connections must be in accordance with local codes, ordinances, or the national electrical code. If you are unfamiliar with methods of installing electrical wiring, retain the service of a qualified licensed Electrician. Before starting the installation, disconnect the power by turning off the circuit breaker or removing the fuse from the fuse box. Turning off the light switch is not sufficient to prevent electrical shock.

Connect the wires from the fixture to the low voltage wires from the power supply. Use UL/CSA listed connectors suitable for the size and type of wire. No loose strands or loose connections should be present.

Incandescent Lamp Replacement:

First, remove the lens. Gently apply downward pressure on the plastic arm of the lamp. The lamp will rise and then can be easily removed. Carefully insert a new lamp into the base and apply downward pressure until solid contact is made. The lens can be re-installed by snapping one end in place and working toward the opposite end, sliding one's hand down the length of the lens.



Any questions on voltage type, maximum wattage, or re-lamping, please call or contact us at:



ROBERTS STEP-LITE SYSTEMS ■ 8100 SW 15th St. ■ Oklahoma City, OK 73128
info@robertsstemplite.com ■ www.robertsstemplite.com
405.728.4895 ■ 800.654.8268 ■ F: 405.728.4878

